Response to Office Action mailed September 23, 2005

Serial No. 10/795,902, filed March 8, 2004

Inventor: Bushey Art Unit: 3677

Page 2

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

Claims 1-14. (Cancelled)

15. (Currently Amended) A door stop for retaining a door having a bottom in a user

selected position, comprising:

a support connectable to the door adjacent the bottom, the support including first and

second sides, each side including a plurality of vertically spaced, horizontally extending recesses

therein such that each recess in the first side of the support is axially aligned with a corresponding

recess in the second side of the support; and

a stop member pivotably connected to the support and including first and second legs,

each leg having a first free end and an opposite second end, the stop member pivotable between a

first storage position and a second extended position wherein at least a portion of the stop

member is below the bottom of the door[.];

wherein the free ends of the first and second legs are receiveable in corresponding user

selected recesses in the first and second sides of the support and wherein second ends of the first

and second legs of the stop member are interconnected by a pad, the pad engageable with a

supporting surface with the stop member in the extended position.

16. (Original) The door stop of claim 15 further comprising a mounting structure form

interconnecting the support to the door.

17. (Original) The door stop of claim 16 wherein the mounting structure includes an

adhesive.

Claims 18-28. (Cancelled).

{00089507.DOC /}

Response to Office Action mailed September 23, 2005

Serial No. 10/795,902, filed March 8, 2004

Inventor: Bushey Art Unit: 3677

Page 3

29. (Currently Amended) A door stop for retaining a door having a bottom in a user selected position, comprising:

a support connectable to the door adjacent the bottom, the support including first and second sides, each side including a plurality of vertically spaced, horizontally extending recesses therein such that each recess in the first side of the support is axially aligned with a corresponding recess in the second side of the support;

a retaining structure for retaining the support on the door; and

a stop member pivotably connected to the support and including first and second legs, each leg having a first free end and an opposite second end, the stop member pivotable between a first storage position and a second extended position wherein at least a portion of the stop member is engageable with a supporting surface below the bottom of the door[.];

wherein the free ends of the first and second legs are receiveable in corresponding user selected recesses in the first and second sides of the support and wherein second ends of the first and second legs of the stop member are interconnected by a pad, the pad engageable with a supporting surface with the stop member in the extended position.

30. (Original) The door stop of claim 29 wherein the retaining structure includes an adhesive.

Claims 31-44. (Cancelled).

42. (Currently Amended) A door stop for retaining a door having a bottom in a user selected position, comprising:

a generally flat support member having an inner surface for positioning adjacent a portion of the door adjacent the bottom, an outer surface, and first and second sides; and

a stop member pivotably connectable to the support member at a user selected one of a plurality of axially spaced mounting points, the stop member pivotable between a first storage position and a second extended position wherein at least a portion of the stop member is below the bottom of the door[.];

wherein:

Response to Office Action mailed September 23, 2005

Serial No. 10/795,902, filed March 8, 2004

Inventor: Bushey Art Unit: 3677

Page 4

the mounting points are defined by a plurality of vertically spaced, horizontally extending recesses provided in each side of the support member;

the stop member includes first and second legs, each leg having a first free end and an opposite second end; and

the free ends of the first and second legs are receivable in corresponding user selected recesses in the first and second sides of the support member;

second ends of the first and second legs of the stop member are interconnected by a pad, the pad engageable with a supporting surface with the stop member in the extended position.

- 43. (Previously Presented) The door stop of claim 42 further comprising a mounting structure for interconnecting the support member to the door.
- 44. (Previously Presented The door stop of claim 43 wherein the mounting structure includes an adhesive.

Claim 45. (Cancelled).

- 46. (Currently Amended) The door stop of claim [45] <u>42</u> wherein each recess in the first side of the support member is axially aligned with a corresponding recess in the second side of the support member.
- 47. (Currently Amended) The door stop of claim [45] <u>42</u> wherein each recess in the first side of support member communicates with a corresponding recess in the second side of the support member.

Claims 48-49. (Cancelled).